

FLO-GARD® 6201 Volumetric Infusion Pump

The Leading Edge in Standard Set Infusion Pump Technology

- Selectable Options offer customized control of operation
- Computer Interface allows remote operation and monitoring



THE EVOLUTION CONTINUES...

Baxter
Flo-Gard® 6201
VOLUMETRIC INFUSION PUMP

FOR SINGLE-CHANNEL CAPABILITY

FLO-GARD® 6201

Volumetric Infusion Pump

Enhanced Safety

- *Flow Check Occlusion Alarm*-an in-line resistance display of incremental back pressure
- *Flow Rate Calculation* is automatic after volume and time are selected
- *Slide Clamp Option* offers an additional step to protect against inadvertent gravity free flow
- *Front Panel Lock-out* protects against tampering

Greater Convenience and Versatility

- *Programmed Delivery Profile* allows up to 10 steps, individualizing control of infusion ramping and tapering
- *Incremental Flow Rate* can deliver 1-99.9 mL /hr in increments of 0.1 mL /hr
- *Automatic Restart* once occlusion clears
- *Automatic Piggybacking* of secondary medications

Cost-Efficiency

- *Uses Baxter standard administration sets*
 - eliminates the need for costly disposable sets
 - reduces potential for waste

Baxter

Selectable Options for Customized Control

PARAMETER	CHOICES
• Flow Check Display	On/Off
• Occlusion levels	3 levels of sensitivity
• Automatic Restarts	09
• Alarm/Alert Intervals	1-7 seconds
• Hospital Area Designator	9 choices preprogrammed
• Slide Clamp Option	On/Off
• Air-In-Line Detection	2 levels of sensitivity
• Maximum Rate	1-1,999 mL/hr
• VTBI Range	1-9,999 mL
• Computer Control	On/Off
• Baud Rate	300, 1200, 2400, 4800,9600

Performance Capabilities

• Flow Rate Range	1-99.9 mL/hr in 0.1 mL/hr increments and 1-1,999 mL/hr in 1 mL/hr increments
• VTBI Range	1-9,999 mL
• Alarm Log	Last 10 alarms

Physical Specifications

• Dimensions	20cm W x 13cm D x 29 cm H (8 in Wx 5.1 in D x 11.4 in H)
• Weight	5.3kg (11.6 lb)
• Battery	12 volt, 2.0 ampere, sealed lead acid
• Battery Recharge	80% charged within 8 hr
• Battery Life	6 hr at 1,400 mL/hr
• Power Cord	Biomed replaceable 2.9m (9ft)
• Leakage Current	less than 50 micro-amps (per UL544)
• Fuse	1/2 ampere, 250 volt slow-blow
• Communications Port	R5232 serial port
• Operating Environment	15.5 – 40.6°C (60-105°F)
• Power Requirements	115 VAC,60Hz,30W